



# Winston Battery


Address: Winston Industrial Park, Third Industrial Zone, Lisonglang Village,  
Gongming Town, Shenzhen, Guangdong, P.R.C  
Tel: +86-755-8602 6789 Fax: +86-755-8602 6678  
Http: //www.winston-battery.com E-mail: winston@winston-battery.com

## 燃油汽車起動專用鋰電池技術說明 SPECIFICATIONS OF LI-ION STARTING-UP POWER BATTERY FOR FUEL CAR

### 單體電池尺寸 DIMENSIONS



型号(MODEL): WB-LP12V60AH




### 技術參數 SPECIFICATIONS

型號(MODEL)	WB-LP12V60AH	
標稱容量 Nominal Capacity	60AH	
規格 SPEC	長 L	282mm
	寬 W	125mm
	高 H	230mm
工作電壓 Operation Voltage	充電 Charge	16(V)
	放電 Discharge	11(V)
內阻 Internal resistance	≤3(mΩ)	
最大放電電流 Max Discharge Current	恒電流 Constant Current	≤3CA
	脈衝試 Impulse Current	≤10CA
最大充電電流 Max Charge Current	180A(3CA)	
標準充放電電流 Standard Charge/ Discharge Current	30A(0.5CA)	
使用壽命 Cycle Life	5-10年/Years	
殼體耐溫性 Temperature Durability Of Case	≤200°C	
	充電 Charge	-45°C ~ 85°C
適應環境 Operation Temperature	放電 Discharge	
	存儲濕度 Storage Humidity	≤75%RH
自放電率(月) Self-discharge Rate	≤3% (月/Monthly)	
單體電池重量 Weight	11.5kg ± 200g	


# WB-LP12V60AH型電池的充放電特性

WB-LP12V60AH CHARGE & DISCHARGE CHART



## WB-LP12V60AH在25°C環境下60A充放電特性

WB-LP12V60AH CHARGE AND DISCHARGE BY 60A AT TEMPERATURE OF 25°C



## WB-LP12V60AH在不同溫度環境下的脈衝放電特性

WB-LP12V60AH IMPULSE DISCHARGE AT DIFFERENT TEMPERATURE